

541478

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/062807 A1

- (51) International Patent Classification⁷: **B02C 7/12**
- (21) International Application Number: **PCT/SE2003/001928**
- (22) International Filing Date:
11 December 2003 (11.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0300082-5 14 January 2003 (14.01.2003) SE
- (71) Applicant (for all designated States except US): **METSO PAPER, INC** [FI/FI]; P.O. Box 1220, FIN-00101 Helsinki (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **VIRVING, Nils** [SE/SE]; Backtimjegränd 27, S-165 73 Hässelby (SE).
- (54) Title: **REFINING ELEMENT**
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/062807 A1



(57) Abstract: Refining element for use in refiners for working lignocellulosic fibrous material in a cone-shaped refining gap (6) between two refining means (1, 2) with opposed conical surfaces, where the refining means (1) with the outside located conical surface is stationary, and the refining means (2) with the inside located conical surface is rotary, and the refining element (11) is intended for the stationary refining means (1) and formed with bars (12) and intermediate grooves (13), where the bars extend along the refining gap (6) and are defined by an upper surface (14) and two side surfaces (15, 16). The upper surface (14) of each bar is a portion of the conical working surface of the

refining element (11), and said upper surface (14) forms an acute angle (α) with at least one of the side surfaces (15, 16) of the bar (12).